

710-740W



23.8%



TOPCon



740W

23.8%


1%

0.4%

2-30

N-Type	
132 2×66	
TüV 1×4mm , (+)350mm, (-)280mm	
	2.0mm
	2.0mm
37.1 kg	
2384×1303×33mm	
33	
	660 /13.5 825 /17.5
	594 /40

17.5 28T



* :±2mm :±2mm t:±1mm :±2mm

Pmax/W				540		543		547					
Voc/V	48.91	46.38	49.14	46.56	49.36	46.74	49.55	46.92	49.71	47.10	49.87	47.28	
Isc/A	18.15	14.65	18.19	14.68	18.24	14.71	18.32	14.74	18.38	14.77	18.44	14.80	
Vmp/V	41.50	39.12	41.69	39.27	41.91	39.38	42.10	39.55	42.25	39.74	42.39	39.93	
Imp/A	17.11	13.70	17.15	13.75	17.18	13.79	17.22	13.83	17.28	13.86	17.34	13.89	
%	22.9		23.0		23.2		23.3		23.5		23.7		
1 STC	1000W/M²		25	AM1.5	2 NOCT		800W/M²	20	AM1.5	1M/S			

		5%	10%	20%
STC	Pmax/W	750.8	786.5	858.0
	Voc/V	49.1	49.1	49.1
	Isc/A	19.1	20.0	21.8
	Vmp/V	41.7	41.7	41.7
	Imp/A	18.0	18.9	20.6
	%	24.2	25.3	27.6

*

(Isc)	+ 0.045%/
(oc)	- 0.25%/
(Pmax)	- 0.29%/

-40 ~ +85
0~ +5W
DC1500V IEC
45±2
80±5%
()
IP68

5400Pa
2400Pa
25mm, 23m/s